

Steam Traps

Float-controlled Steam Traps KA 2

Your advantages at a glance



Connection	G 3/4 x 1/2A
Nominal Pressure	PN 16
Operating Pressure	0 - 12 bar
Flow Rate	350 l/h
Temperature	190°C
Medium	Steam

Universal Valve for Small Flow Rates

Soft seal possible for explosive gases, for steam with manual bleeding | suitable for steam, compressed air, aerosols | completely made of deep-drawn CrNiMo steel | very lightweight, corrosion resistant to aggressive media, especially gastight | easy installation, easy and cost-effective maintenance owing to the clamp system, long operational lifespan

www.mankenberg.de | Tel. +49 (0) 451 - 8 79 75 0

MANKENBERG GmbH | Spenglerstraße 99 | D-23556 Lübeck

Sheet no. KA 2/6.1.101.1 issue 01.12.20109



compact, pressure-resistant, corrosion-resistant by deep drawn 316 Stainless steel

long operational lifespan, easy installation, minimum space required, possibly low content of delta-ferrite

standard surface < RA 1,6 µm
easy to clean

Mankenberg clamp system
fast service

pressure and corrosion resistant internal parts of deep drawn CrNiMo stainless steel (Grade 316L)
long operational lifespan

sturdy valve mechanism
low maintenance