

Pumps



Condensate Pump KH 1

Your advantages at a glance

Connection	DN 25 + 50
Nominal Pressure	PN 16
Motive Medium Inlet	G 3/4A
Blow Off Line	G 3/4 A
Lifting Height	40 m
Driving Pressure	up to 8bar
Flow Rate	3430 l/h
Temperature	200 °C
Medium	gases and steam

Very Lightweight Condensate Pump

Soft seal for gas tightness in explosive environments | suitable for condensates and liquids | completely made of deep-drawn CrNiMo steel | very lightweight and compact, corrosion resistant, pump requires no auxiliary energy | manageable installation, easy-to-maintain owing to the clamp system, long operational lifespan, highest effectiveness with compact design

www.mankenberg.de | Tel. +49 (0) 451 - 8 79 75 0

MANKENBERG GmbH | Spenglerstraße 99 | D-23556 Lübeck

Sheet no. KH 1/6.1.101.1 issue 01.12.2010

compressed air, steam or inert gases up to max. 8 bar as blowing agent

sturdy valve mechanism
low maintenance

Mankenberg clamp system
fast service

standard surface < RA 1,6 µm
easy to clean

compact, pressure-resistant, corrosion-resistant by deep drawn 316 Stainless steel, extremely lightweight and compact, only 21 kg of weight at a nominal diameter of DN 50

long operational lifespan, easy installation, minimum space required

inlet and outlet arranged at a low level

